

Incredible **75,000** hrs

### GENERAL DESCRIPTION

Neptun's LED rectangle step-light fixtures feature architectural design and durability to fit new construction and retrofit applications. The LED-ST53 series features a slim design and is surface mounted for easy installation.

### APPLICATION



- Building Accent Lighting
- Landscape Lighting
- Security Lighting
- Step Light Lighting

### STRUCTURE, MATERIALS, & FEATURES

- Die-cast aluminum housing.
- High efficiency, heat and impact resistant, UV protected, non yellowing polycarbonate lens / refractor.
- Corrosion resistant electrocoat grey or black finish.
- Continuous silicone gasketing surrounds lens for weather - tight seal.
- High Output LED's.
- High power factor, low THD driver with 10kV Surge Protection.
- InstantON flicker-free Cold Start and Hot Re-Start.
- Up to 15 years Maintenance free operation.
- 5 Year Warranty on complete fixture. (LED's, Driver, & Housing)

### ORDERING INFORMATION

Sample Number: LED-ST53006-120V-850-BLK  
 Custom options and accessories available. Please consult factory

Series	Wattage	Voltage	Color Temp	Color
LED-ST53 = Step-Light	006 = 0.6 W	120V = 120-265 VAC	835 = 3500°K 841 = 4100°K 850 = 5000°K	BLK = Black  GRY = Grey  * Custom Colors Available



### PRODUCT INFORMATION

Model No.	Description	Rated Watts	Input Watts	Initial Lumens	Line Voltage (VAC)	Max Line Current (Amp) @ 120VAC	THD	Power Factor	Weight
LED-ST53006-120V	LED Step-Light Fixture	0.6	0.8	40	120-265	0.005	<15%	>0.90	1 lbs

### SPECIFICATIONS

- Driver ..... Constant Current
- Start Method ..... InstantON
- Hot Re-start ..... InstantON
- Power Supply ..... 350mA
- Driver UL Rating ..... Class 1
- Driver UL Outdoor Rated ..... Wet Location
- Sound Rating ..... Class A
- ANSI Surge Protection ..... IEEE C62.41 C High
- Driver Off-State Draw ..... 0 Watts
- Input Line Voltage ..... 120-265 VAC
- Input Line Frequency ..... 50/60 Hz
- LED / Driver System Life ..... 75,000 Hrs.
- Lumen Maintenance @50,000Hrs ..... > 70%
- Color Temperature ..... 5,000°K
- Color Rendering Index (CRI) ..... > 80
- Minimum Starting Temperature ..... -40°C
- Maximum Starting Temperature ..... +50°C
- Lumens per Watt ..... > 60
- Shock / Vibration Resistant ..... Yes
- Power Factor ..... > 0.90
- Total Harmonic Distortion ..... < 15%
- Inrush Current Peak ..... < 10 Amp
- FCC Compliance ..... Part 15, Subp. C
- Housing IP Rating ..... IP65
- Warranty ..... 5 Year

### SURFACE MOUNT - SLIM DESIGN



Neptun Light, Inc.  
 13950 Business Center Drive  
 Lake Forest, IL 60045  
 Fax: 847.735.8004

Neptun Light, Inc. reserves the right to change materials or modify the design of its product without notification as part of the company's continuing product improvement program.  
 ©2002-2013 Neptun Light, Inc. All rights reserved.

Spec. Rev. 1-2015